

HD2-B50

2 Megapixel 1080P AVS-HD Technology Water-proof OSD IR HD 2MP Outdoor Box 2 Array 50M NV 6mm

- ◆ 1/3" 2Megapixel CMOS
- ◆ AVS-HD Technology
- ◆ 25/30fps@1080P, 25/30/50/60fps@720P
- ◆ High speed, long distance real-time transmission
- ◆ HD and standard definition switch
- ◆ OSD Menu, control over coaxial cable
- ◆ Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- ◆ 3.6 mm Lens
- ◆ Max. IR LEDs length 50m, Smart IR
- ◆ IP66, DC12V



SPECIFICATIONS

CAMERA

Image Sensor	1/3" 2 Megapixel CMOS
Effective Pixels	1920(H)×1080(V)
Electronic Shutter	1/3(s)~1/100,000s
Video Frame Rate	1920×1080@25 fps 1920×1080@30 fps 1280×720@25 fps 1280×720@30 fps 1280×720@50 fps 1280×720@60 fps
Synchronization	Internal
Min. Illumination	0.05Lux@F1.2(0Lux IR LED on)
Video Output	1-channel BNC AVS-HD high definition video output / CVBS standard definition video output (Can switch)

CAMERA FEATURES

Max. IR LEDs Length	50m, Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D/3D
OSD Menu	Support

LENS

Focal length	3.6mm
Mount Type	M12

GENERAL

Power Supply	DC12V±10%
Power Consumption	Max 8W
Working Environment	-30°C~+60°C/ Less than 95%RH (no condensation)
Transmission Distance	Over 300m via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions (W×D×H)	Φ200.2mm×89.1mm×80.4mm
Weight	450g

