

4 Ch HD-AVS DVR 720P @ 30fps & 2 Channel 2MP IP Recording



OVERVIEW

- 1.3 MP/720p @ 30fps View & Recording
- 2 Channels of IP Recording 2 MP/1080p @ 15fps
- H.264 dual-stream video compression
- HDMI / VGA simultaneous video output
- 1 Ch Audio In/Output
- ONVIF Version 2.4 conformance
- No Alarm Integration
- Support 1 SATA HD up to 6TB, 2 USB2.0
- Includes 1 TB Hard Drive

Panther-4E-TRI

Main Processor: Embedded processor
Operating System: Embedded LINUX
Standard Input: 4 channel, BNC
HDCVI Input: 1080P/720P HDCVI Camera
IP Input: Support 2ch 1080P/720P IP Camera
Audio Input: 1 channel, RCA
Output: 1 channel, RCA
Two-way Talk: Reuse audio input/output channel 1
Display Interface: 1 HDMI, 1 VGA
Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768
Display Split: 1/4
Privacy Masking: 4 rectangular zones (each camera)
 OSD Camera title, Time, Video loss, Camera lock, Motion de-
 tection, Recording
Recording Video/Audio Compression: H.264/G.711
Main Stream: 1080P(1~15fps) / 720P / 960H / D1 (1~30fps)
Extra Stream: CIF/QCIF(1~30fps)
Bit Rate: 96~4096Kb/s
Record Mode: Manual, Schedule(Regular(Continuous), MD), Stop
Record Interval: 1~60 min (default: 60 min)
Pre-record: 1~30 sec
Post-record: 10~300 sec
Video Detection & Alarm Trigger: Recording, PTZ, Tour, Alarm
 out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Video Detection: Motion Detection, MD Zones: 396(22×18),
 Video Loss & Camera Blank

Search Mode: Time/Date, MD & Exact search to the second
Playback Functions: Play, Pause, Stop, Rewind, Fast play, Slow
 play, Next file, Previous file, Next camera, Previous camera,
 Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Sync Playback: 1/4
Backup Mode: USB Device/Internal SATA burner/Network
Network Ethernet: RJ-45 port (10/100M)
Network Functions: HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP,
 UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter,
 SNMP, P2P
Max. User Access: 128 users
Smart Phone: iPhone, iPad, Android, Windows Phone
Storage: Internal HDD 1 SATA port, up to 4TB
Auxiliary Interface: USB Interface 2 ports(1 Rear), USB2.0,
 RS485 1 port, For PTZ Control
Power Supply: DC12V/2A
Power Consumption: 10W(without HDD)
Working Environment: -10°C ~+55°C / 10%~90%RH /
 86~106kpa
Dimension: (W x D x H) Mini 1U, 12.79 x 10.03 2.16 inches
Weight: 3.30lbs (without HDD)

4 Ch HD-AVS DVR

Panther-4E-TRI

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064

**7 YEAR
WARRANTY**

**FREE
LIFETIME
SUPPORT**

