

Panther 5 Megapixel Penta-brid 32 Ch HD-AVS DVR with 4 TB


5 IP
 HD Analog
 Analog
 TVI
 CVI
PENTA-BRID



Panther5-32

Main Processor: Embedded LINUX Processor
Display Interface: 2 HDMI, 1 VGA, 1 TV
Resolution: 1920x1080, 1280x1024, 1280x720, 1024x768
Multi-screen Display: 1/4/8/9/16/25/36
OSD: Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Trigger Events: Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection: Motion Detection, MD Zones: 396 (22 x 18), Video Loss, Tampering and Diagnosis
Alarm input: 8/16/16
Relay Output: 6
Tracking Trigger Event: N/A
Playback: 1/4/9/16
Search Mode: Time /Date, Alarm, MD and Exact Search (accurate to second), Smart search
Playback Function: Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode: USB Device/Network
Internal HDD: 4 SATA Ports, up to 8TB capacity for each disk
HDD Mode: Single
eSATA: 1 Port
USB: 3 USB Ports (1 USB 2.0, 2 USB 3.0)
RS232: 1 port, for PC communication & Keyboard
RS485: 1 Port, for PTZ Control
Third-party Support: ClearView, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sa, yo, Sony, Videotec, Vivotek, and more

OVERVIEW

- 32 Ch 5 Megapixel HD-AVS DVR
- H.265 / H.264 Dual-stream video compression
- Support HD-AVS/IP/HD-TVI/Analog/HD-Analog
- Max 24 ch IP camera inputs, up to 5MP per ch
- Max 96Mbps Incoming Bandwidth
- Smart Search and Intelligent Video System
- 2 SATA Ports
- Supports up to 6TB capacity for each disk
- Includes 4 TB Hard Drive

HD-AVS Camera Input: 8/16/32 Channel
IP Camera Input: 16 Channel, each channel up to 5MP
Audio In/Out: 4/1
Two-way Talk: 1 Mic In, 1 Mic Out, BNC
Recording Compression: H.265/H.264
Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF
Record Rate: Main stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Sub stream:D1/CIF/QCIF(1~15fps)
Bit Rate: 1Kbps ~ 6144Kbps Per Channel
Record Mode: Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop Record
Interval 1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec
Network Interface: 1 RJ-45 Port (1000M)
Network Function: HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search (Support ClearView IP camera, DVR, NVS, etc.)
Max. User Access: 128 users
Smart Phone: iPhone, iPad, Android
Interoperability: ONVIF 2.4.1, CGI Conformant
Power Supply: AC100V-240V, 50/60Hz
Power Consumption: <30W (Without HDD)
Operating Conditions: +14°F ~ +131°F, 86 ~ 106kpa
Storage Conditions: +32°F ~ +122°F, 0 ~ 90% RH
Dimensions: 1.5U, 17.3" x 16.4" x 3.0"
Net Weight: 13.23lb (without HDD)
Gross Weight: 15.43lb

Access Anywhere

Android

iPhone

Most OS



7 YEAR WARRANTY

FREE LIFETIME SUPPORT

32 Ch HD-AVS Penta-Brid DVR

Panther5-32

www.ClearViewCCTV.com Phone: 855-248-7888 3050 N Andrews Ave Ext. Pompano Beach, FL 33064