

8 Channel NVR Complete Kit with Four IP 1.3 Megapixel Cameras & 4 PoE Ports



OVERVIEW

- 8 Channel NVR
- Four 720P H.264 IP Cameras
- Expandable to 8 Cameras
- 8 PoE Ports
- IP67 Weather-Proof
- PoE Power Over Ethernet
- 100 ft IR NightVision Range
- Includes 1 TB Hard Drive

Control (4)







PhoenixView-08-4D

Main Processor: ARM Dual-core embedded processor

Operating System: Embedded LINUX Display Interface: 1 HDMI, 1 VGA

Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768

Multi-screen Display: 1/4/8/9

OSD: Title, Time, Video loss, Camera lock, Motion detection, Recording Trigger Events: Recording, PTZ, Tour, Video Push, Snapshot, Buzzer and Screen Tips

Video Detection: Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Tampering

Sync Playback: 1/4/9

Search Mode: Time / Date, MD and Exact Search to THE second Playback Function: Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom

Backup Mode: USB Device/Network/Internal SATA burner Internal HDD: 1 SATA III Port, up to 6TB capacity for each HDD **USB:** 2 ports (2 Rear USB2.0)

IP Camera Input: 8 Channel

Two-way Talk: 1 Channel Input, 1 Channel Output, RCA

Recording Compression: H.264+/H.264 **Resolution:** 4Mp/3Mp/1080P/ 720P/ D1&etc.

Record Rate: 80Mbps

Bit Rate: 16kbps~20Mbps for per channel

Record Mode: Manual, Schedule(Regular(Continuous), MD, Stop Record Interval: 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Network Interface: 1 RJ-45 port (10/100Mbps) Ethernet Port: 1 Independent 100Mbps Ethernet Port

PoE: 8 ports 80wat total (IEEE802.3at/af)

Network Function: HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search(Support CV IP camera, DVR, NVS and etc.), Easy4ip

Smart Phone: iPhone, iPad, Android

Interoperability: ONVIF 2.4, CGI Conformant

Power Supply: Single, DC48V/2A

Power Consumption: NVR: <4.5W (without HDD)

Operating Conditions: -10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa

Storage Conditions: -20°C ~ +70°C, 0 ~ 90% RH Dimensions(W xD xH): Smart 1U,10.6" x 8.1" x 1.8"

IPD-70 IP 1.3 MEGA-PIXEL IR INFRARED DOME CAMERA SPECS:

- 1/3" 720P 1.3 Megapixel progressive scan CMOS
- H.264 / MJPEG dual-stream encoding
- Max 30fps @ 1.3 Megapixel (1280x960)
- Day/Night(ICR), 3DNR, AWB, AGC, BLC, DWDR
- 3.6mm Angle Lens
- IP67 Weather-Proof
- PoE Power Over Ethernet
- 100 ft Ir nightvision Range









